

Dynacom NHQ512IR **STARVIS IP Mini Speed Dome Camera**


1/2.8" progressive scan CMOS
STARVIS Image Sensor
12x optical zoom, 16x digital zoom
4.7 ~ 56.4 mm
5MP(2560×1920) @ 25/30fps
Multiple streams
3D DNR, WDR, ICR, IVS, Defog
Auto tracking
Smart IR range up to 80 m
IP66



Excellent Video Compression

Smart encode, the advanced video codec, saves 60% ~ 80% bandwidth compared with H.264.

Smart Encode




H.264



Smart IR

Dynacom smart IR technology used High Beam and Low Beam combination, for better image clarity and quality regardless of the object distance. Also, the Low Beam and High Beam's brightness can be adjusted manually or automatically on the basis of the zoom ratio.



Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	2560 (H) x 1920V
Electronic Shutter	Auto/Manual, 1/5 ~ 1/20,000s
Min. illumination	Color: 0.01 Lux @ (F1.2, AGC ON), B/W: 0 Lux @ (IR LED ON)
S/N Ratio	55 dB
Day/Night	Auto(ICR)/Day / Night/Timing
Wide Dynamic Range	WDR 120 dB
IR Range	Smart IR, Up to 80 m (262.5 ft)
IR On/Off Control	Auto/Manual
Lens	
Focal Length	4.7 ~ 56.4 mm
Max. Aperture	F1.6 ~ F3.0
Angle of View	H: 60.9°~6.43°, V: 40.1°~4.1°
Optical Zoom	12x
Digital Zoom	16x
Focus Control	Auto/Manual
PTZ	
Pan/Tilt Range	Pan: 0° ~ 360° endless, Tilt: -10° ~ +90°
Manual Control Speed	Pan: 0.1° ~ 180°/s, Tilt: 0.1° ~ 90°/s
Preset Speed	Pan: 180°/s, Tilt: 90°/s
Presets	300
PTZ Mode	6 Track, 12 Tour, 12 Scan,
Speed Setup	Auto/Manual (0-8)
Power up Action	Support
Idle Motion	Activate Preset/ Scan/ Tour/ Track if there is no command in the specified period
Video	
Max. Resolution	5MP (2560×1920)
Streaming Capability	3 Streams
Stream/Frame Rate	Stream1: 2560×1920/2048×1536/1280×960 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @ 25/30fps Stream3: VGA/CIF/QVGA @ 25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 200kbps~12Mbps / Stream2: 10kbps~6Mbps / Stream3: 10kbps~3Mbps
Image Enhancement	HLC/BLC/Anti-shake/Defog /WDR
Noise Reduction	2D/3D DNR
Region of Interest	Off/On (8 Zone, Rectangle)
Motion Detection	Support
Privacy Masking	Off/On (4 Area, Rectangle)

Dynacom

No.15-1 Zhonghua Road, Hsinchu Industrial Park,
Hukou, Hsinchu, 30352, Taiwan
31082 San Antonio St, Hayward, CA, 94544, USA
www.dynacom.tw info@dynacom.tw

Audio	
Audio Compression	G.711, RAW_PCM
Bit Rate	8kbps(G.711), 16kps(RAW_PCM)
Network	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP
Interoperability	ONVIF, SDK, CGI
Streaming Method	Unicast
Max. User Access	10 Users
Edge Storage	Local PC for instant recording, Micro SD card 256GB
Web Viewer	<IE11, Chrome, Firefox
Intelligence	
Auto Tracking	Support
IVS	Perimeter, Single Virtual Fence, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio	1ch Input, 1ch Output
Alarm	2ch Input, 1ch Output
Reset Button	Yes (Built-in)
Electrical	
Power Supply	DC12V/POE+ (IEEE 802.at)
Power Consumption	Less than 25 W
Operating Temperature	Starting Temperature: -40°C ~ 60°C (-40°F ~ 140 °F)
	Working Temperature:-55°C ~ 60°C (-67°F ~ 140 °F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP66, TVS4000V
Certifications	CE/FCC
Casing	Metal
Dimensions	146.6 × 139.3 × 218.3 mm (5.77 × 5.48 × 8.59 inch)
Net Weight	1.5 kg (3.31 lb)

Dynacom

No.15-1 Zhonghua Road, Hsinchu Industrial Park,
Hukou, Hsinchu, 30352, Taiwan
31082 San Antonio St, Hayward, CA, 94544, USA
www.dynacom.tw info@dynacom.tw