

Dynacom NHQ20-IR 2 M 20x Zoom Speed Dome Camera



- 2MP intelligent IR network high speed dome camera
- H.264/MJPEG
- 1080/960/720P, 20X optical zoom F=4.7~84.6mm
- Manual control speed: 0.1-150°/S, preset speed: 200° / S
- Horizontal continuous rotate 360°, 90° vertically rotation
- IR irradiation distance 100m
- 256 preset, 6 cruise

Model No.	NHQ20-IR
CAMERA	
Pick-up device	1/3 inch CMOS
Effective Pixels	1920(H) x 1080(V)
Video Output	1080P/30, 1080P/25
Min. Illumination	Color: 0.05 Lux/F1.6, B/W: 0Lux/F1.6(IR ON)
Scanning system	Progressive scan
Sync System	Internal
S/N Ratio	50dB
White Balance	ATW / AWC / INDOOR / OUTDOOR / Manual
Day&Night	Auto, COLOR, B/W(ICR)
Electronic shutter	AUTO / MANUAL
AGC	x1/x2/x4/x8/x12/x16/x24/x32/x64
BLC	OFF/ ON/ BLC
Mirror	OFF/ H-Mirror/ V-Mirror
SSNR	High/ Mid/ Low/ OFF
LENS	
Zoom	20X optical zoom
Focal Length	f=4.7 to 84.6mm(F1.6~F2.7)
Focus	Auto/Manual
Iris	Auto/Manual
FUNCTION	
Network Protocols	HTTP,SMTP,DHCP,DNS,DDNS,NTP,FTP,Qos,TCP,HTTPS,IGMP
Dual-stream	Support
Network Interface	RJ45 ,support 10M/100M network data
API	Support software integration open type API, Standard Protocol (Onvif)
Web Browser	Support IE7、IE8、IE9、IE10 and based on the IE core browsers
Smart Phone Client	Apple, Windows, Blackberry, Android, etc
Horizontal	360° Endless
Vertical	0°~90° Auto rotation
Pan / Tilt Speed	Preset: 200°/sec, Manual:0.1°-150°/S
Preset Accuracy	0.1°
Soft/Hard add	Support
Address	0-255
Preset	256
Pattern	Support
Cruise	6
Group	4
Auto Scan	Support
Power up action etc	Support
Home Function	Support
IR irradiation distance	100M
IR irradiation angle	Adjustable by zoom
Alam Input	2
Alarm Output	1
Alarm Linkage	Preset/Cruise/Pattern
OSD Menu	Support
ENVIRONMENT	
Power supply	DC12V 4A
Power	35W
Operating Temp	-30°C~60°C
Humidity	0%~90%
Size	272(H)*190(D)mm
Application environment	Outdoor
Water proof	IP66
Weight	3.3KG



2 MP

