

Dynacom WQ960 Series Bullet Camera

5M pixel
 2560x1920
 1/2.8"SONY Starvis Back-illuminated CMOS sensor
 2.7-13.5mm Lens, 5x Optic zoom, 6x Digital zoom
 E-PTZ
 Motor Zoom Auto Focus Lens
 Built-in IR-CUT.Low power consumption
 IR Distance 50m Max.
 Micro SD 512GB support
 H.264/H.264+/H.265/H.265+/JPEG/MJPEG Compression Method
 Support Multiple-Stream
 Support ONVIF protocol
 IP67 Outdoor Metal Case



CAMERA		
Model	WQ960ZV	WQ960ZAI
Case	Metal, Bullet	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	
Max Resolution	5M / 2560x1920	
Min. illumination	0.01Lux @ F1.2 (Color) (0 Lux IR LED On)	
Day / Night	Day / Night with ICR Filter.	
IR Leds	42μ x 4pcs*, IR Range: 50M	
Lens	2.7 -13.5mm Motorized Lens, 5x Optic Zoom	
Focus	Auto Focus	
Video Output	Main stream: 2560*1920@20fps / 2560*1440@25fps / 1920x1080@30fps	
	Sub stream: 720*480@30fps	
	Tri stream: 352*288@30fps	
PARAMETERS		
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG	
Bit Rate (CBR/VBR)	32Kbps-16Mbps continuously adjustable, support CBR/VBR	
WDR	140dB	
Image Setting	Brightness, Sharpness, Contrast, White Balance, Exposure Control, 2DNR, 3DNR, High Light Compensation, Masking, Text Overlay	
Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	
S/N Ratio	≥55dB	
NETWORK		
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption	
Standard protocol	Onvif 2.4	
Network Protocols	IPv4/v6,TCP/IP,UDP,ICMP,IGMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SSL,SMTP,SNMP,UPnP, PPPoE, VLAN, SIP, 802.1x, QoS	
Mobile phone monitor	Support mobile phone monitor (iPhone, iPad, Android, Android Pad)	
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari	
AI FUNCTION		
Intelligent Analysis	Motion Detc., Tampering Alarm	Intrusion Detc., Line Cross Detc., Loiter Detc., People Gather Detc.,
CONNECTOR		
Audio Input (Optional)	1CH audio MIC input/Line in	
Audio Output (Optional)	1CH audio output	
Reset Button	Optional	
Alarm in/output (Optional)	1* Alarm input port/1*Alarm output port	
SD Card	Micro SD 512GB	
GENERAL		
Power	DC12V±10%, 950mA	
Working Temperature	-40°C ~ +60°C RH95% Max	
Housing	Metal, IP67	
Product Dimensions	179(W) x 90(H) x 90(D)mm	
Weight	1400g	