

Dynacom DN6025F SERIES 25CH 960P/16CH 1080P 4HDD NVR



- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free



| | | |
|-----------------------------------|---|--|
| Model Number | Dynacom DN6025F | |
| Operating System | Embedded LINUX operating system | |
| Image Code Control | Image code quality adjustable, variable bitstream and constant bitstream optional | |
| Dual Stream | Each channel can set main stream and sub stream | |
| Video Standard | 1080P(1920×1080)30fps/ 960P(1280×960)/720P(1280×720)30fps | |
| Monitoring Image Quality | 1080P(1920×1080) / 960P(1280×960)/720P(1280×720) | |
| Image Motion Detection | Each screen can set multiple detection areas and set 6-level sensitivity | |
| Recording Playback Quality | 9ch 960P/720P playback, 4ch 1080P/3MP/5MP playback | |
| Region Cover | Every channel can set 4 cover regions (IPC Support) | |
| Recording Mode | Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support) | |
| Backup Way | Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup | |
| Operation Way | Mouse | |
| Local Login | User name and password | |
| Recording Storage | Local HDD, network | |
| External Ports | Video Input | ①25×(1280*960)+sub[720*576]+4Ref.+9Play 25ch 1.3MP IP Camera ②16×1920*1080)+sub[720*576]+4Ref.+4Play 16ch 2.0MP IP Camera ③8×(2048*1536)+sub[960*576]+4Ref.+4Play 8ch 3.0MP IP Camera ④4×(2592*1944)+sub[960*576]+4Ref.+4Play 4ch 5.0MP IP Camera |
| | Audio Input | 25/16ch network audio input |
| | Video Output | 1ch VGA+1ch HDMI |
| | Audio Output | 1ch RCA output |
| | Network Port | 1 RJ45,10M/100M/1000M self-adaptive LAN port |
| | RS485 Port | Full duplex standard 485 port |
| | USB Port | 1 USB 3.0 port, 2 USB 2.0 ports |
| | Alarm Input | 4ch |
| | Alarm Output | 1ch |
| | Wireless Port | 3G, WIFI |
| HDD | HDD Port | 4 SATA HDD Port |
| | MAX Capacity | Each port supports MAX 4TB HDD |
| Mobile Surveillance | Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone | |
| Power Supply | 12V6A | |
| Power Consumption | ≤25W (without HDD) | |
| Working Temperature | -10°C~ +55°C | |
| Working Humidity | 10%-90% | |
| Dimension | Equipment : 440mm×360mm×70mm, Packing : 460mm×135mm×560mm | |
| Weight(without HDD) | N.W. : 5.7Kg ; With packing : 6.9Kg | |
| Outside Carton | 4 pcs/carton. 480mm×560mm×575mm ; Weight : 30 Kg | |
| Installation Way | Desktop Installation | |